

# TECHNICAL DESCRIPTION GARAGE

## 1. TECHNICAL SPECIFICATIONS OF THE BUILDING

# 1.1. Load bearing building structures

Foundation: monolithic, waterproof reinforced concrete slab foundation

Vertical structures: monolithic reinforced concrete pillar frame, reinforced con-

crete stairwell and lift core, with 30 cm thick infill walls

Ceiling slabs: intermediate floor slabs and top slab monolithic reinforced

concrete flat plate

Stair structures: monolithic reinforced concrete

#### 1.2. Roof structure

Non-walkable flat roof: water and thermal insulation layer covered by 6 cm thick frac-

tionated round-stone gravel load with a stone size of R16-32 mm, with 40x40x4 cm frost-resistant concrete paving stones

on the service walkways

# 1.3. Stairwell, thoroughfares

Floor: colored in material crushed granite floor tiles (minimum 8 mm

thick)

Wall: 2-layer white emulsion wall paint on rendered, plaster

skimmed brick surface and reinforced concrete surface

Ceiling: white emulsion paint on a plaster-skim surface, with heat insu-

lation of a thickness determined in line with the building's en-

ergy dynamics on the underside of the ground floor slab

Building entrance door: custom-made aluminum and glass portal structure with auto-

matic closer, with opening by proximity card and key, or from

within the apartment using the door phone

Internal community doors: non-combustible metal door, fire or smoke protection doors as

prescribed in the building permit

## 1.4. Lift

Quantity: one elevator in each stairwell (4 in total) SCHINDLER 3300

without machine room, counterweight operated elevator cage

Structure: steel fixtures, doors, and external lined coverings

Capacity: 15 persons, 1125 kg load-bearing capacity

## 2. PARKING GARAGE

# 2.1 Non load bearing structures

Floor: reinforced concrete, non-sloping construction with synthetic

resin sheathing, dilated, with floor drain sewers

Wall: exposed reinforced concrete

Ceiling: thermal insulation panels according to thermal design, uncol-

ored reinforced concrete slab

#### 2.2 Doors and windows

Garage door: garage door with ventilation grills, GSM operated opening,

control center and light barrier operated automatic closing with

premature closing prevention

Fire door – basement level: garage door installed at the fire-section boundary within the

underground parking garage, opening-closing sideways, com-

pliant with fire protection regulations

Garage door height: available opening height of the garage door is 220 cms, vehi-

cles exceeding this height are not allowed to enter the parking

garage

Stairway doors: non-flammable, non-locking metal doors

## 2.3 Engineering, lighting

Ventilation: central extraction vents with pressure sensor control, perma-

nent depression in the branch sewer. Air is extracted above the

ceiling plane

Safety system: CO system for the safe extraction of exhaust gases and an au-

tomatic fire alarm system is installed in the common spaces of the basement level parking garage, alert signal to the concierge

service

Lighting: lights on the ceiling with motion sensor switching plus perma-

nent emergency lights

Heating: the parking garage is not temperature controlled

## 2.4 Conditions of use

Vehicle types: the parking garage has been designed to accommodate motor-

cycles and cars, car parking spots however are NOT sufficient to accommodate every vehicle certified as a motor-car by the law. Parking of cars exceeding 470 cms in length may not be possible. Reduced size slots are marked on the design plan, the

width or length is shorter than average

Gas powered cars: gas powered cars are not permitted to use the parking garage

for fire protection and safety reasons

Buyer has received the present technical description from the Seller and understood its contents and, regarding the property described herein and pursuant to the stipulations of the sales contract concluded between the Parties, accepts its terms.

In approval of the present technical description, The Parties have signed the present agreement as it is in full accordance with their contractual will.

Budapest, 2023.

Metrodom Bosnyák 14-18. Kft. Seller Buyer

Buyer